

HOSPITAL GRADE ●
CATALOG



HOSPITAL GRADE ● CATALOG

TABLE OF CONTENTS

Hospital Grade Molded Cords	3
Custom Cord Configurator	5
NEMA Hospital Grade Plugs	6
NEMA Straight Blade Hospital Grade Connectors.....	8
NEMA Hospital Grade Receptacles.....	10

Hubbell Special Orders

Hubbellock® Plugs and Connector Bodies	13
Explosion Proof Plug	13
Wallplates	13
Hazardous to Non-hazardous Location Receptacle Conversion Kits.....	14
Receptacles	14
Mobile X-Ray Plugs	15
Mobile X-Ray Accessory	15
Mobile X-Ray Receptacles	16



NEMA Hospital Grade Plugs

NEMA 5-15 male Plug Angled Up Hospital Grade



Jacket.....SJT Shielded
 Gauge/Wires..... 14/3
 Volts 125V
 Amps 15 Amps
 Color Black
 3 feet..... Product # 3847
 6 feet..... Product # 4204
 15 feet.... Product # 9290

Jacket.....SJT
 Gauge/Wires..... 18/3
 Volts 125V
 Amps 10 Amps
 Color Gray/Clear
 6 feet..... Product # 8548
 10 feet.... Product # 9915

NEMA 5-15 male Plug Angled Left Hospital Grade



Jacket.....SJT Shielded
 Gauge/Wires..... 14/3
 Volts 125V
 Amps 15 Amps
 Color Black
 3 feet..... Product # 3887
 6 feet..... Product # 4207
 15 feet.... Product # 9294

Jacket.....SJT
 Gauge/Wires..... 18/3
 Volts 125V
 Amps 10 Amps
 Color Gray/Clear
 6 feet..... Product # 8546

NEMA 5-15 male Plug Angled Right Hospital Grade



Jacket.....SJT Shielded
 Gauge/Wires..... 14/3
 Volts 125V
 Amps 15 Amps
 Color Black
 3 feet..... Product # 4132
 6 feet..... Product # 4293
 15 feet.... Product # 9291

Jacket.....SJT
 Gauge/Wires..... 18/3
 Volts 125V
 Amps 10 Amps
 Color Gray/Clear
 6 feet..... Product # 8547
 10 feet.... Product # 9914

NEMA 5-15 male Plug Angled Down Hospital Grade



Jacket.....SJT Shielded
 Gauge/Wires..... 14/3
 Volts 125V
 Amps 15 Amps
 Color Black
 3 feet..... Product # 3883
 6 feet..... Product # 4205
 15 feet.... Product # 9293
 Color White
 3 feet..... Product # 4475
 6 feet..... Product # 4949

Jacket.....SJT
 Gauge/Wires..... 14/3
 Volts 125V
 Amps 15 Amps
 Color Black
 6 feet..... Product # 7139

Jacket.....SJT
 Gauge/Wires..... 18/3
 Volts 125V
 Amps 10 Amps
 Color Gray/Clear
 10 feet.... Product # 9912
 Color Black
 6 feet..... Product # 8545

**NEMA 5-15 male
Plug to C13 Angled
Hospital Grade**



Amps.....15 Amps
 Jacket..... SJT
 Gauge/Wires..... 14/3
 Volts..... 125V
 Color..... Black
 Length 10 feet
 Left..... Product # 1041
 Right Product # 1043
 Down Product # 1036
 Up..... Product # 1030

Amps.....10 Amps
 Jacket..... SJT
 Gauge/Wires..... 18/3
 Volts..... 125V
 Color..... Gray/Clear
 Length 10 feet
 Left..... Product # 9916
 Right Product # 9917

**NEMA 5-15 male
Plug to C13 Hospital
Grade**



Jacket.....SJT Shielded
 Gauge/Wires..... 18/3
 Volts 125V
 Amps 10 Amps
 Color Black
 15 feet.... Product # 9288

Gauge/Wires..... 14/3
 Volts 125V
 Amps 15 Amps
 Color Black
 15 feet.... Product # 9287

Jacket.....SJT
 Gauge/Wires..... 18/3
 Volts 125V
 Amps 10 Amps
 Color Black
 6 feet..... Product # 1016
 10 feet.... Product # 1017

Gauge/Wires..... 14/3
 Volts 125V
 Amps 15 Amps
 Color Black
 6 feet..... Product # 1019
 10 feet.... Product # 1023

Gauge/Wires..... 14/3
 Volts 125V
 Amps 10 Amps
 Color Gray/Clear
 10 feet.... Product # 9918

**NEMA 5-20 male
Plug to C19 Hospital
Grade**



Jacket.....SJT Shielded
 Gauge/Wires..... 12/3
 Volts 125V
 Amps20 Amps
 Color Black
 15 feet.... Product # 9301

Jacket.....SJT
 Gauge/Wires..... 12/3
 Volts 125V
 Amps20 Amps
 Color Black
 6 feet..... Product # 4855
 10 feet.... Product # 4856

**NEMA 5-20 male
Plug Angled Up to
C19 Hospital Grade**



Jacket.....SJT
 Gauge/Wires..... 12/3
 Volts 125V
 Amps20 Amps
 Color Black
 3 feet.....Product # 4835
 6 feet.....Product # 4836

NEMA 6-15 male Plug to C13 Hospital Grade



Jacket.....SJT Shielded
 Gauge/Wires..... 14/3
 Volts 250V
 Amps 15 Amps
 Color Black
 15 feet.... Product # 9302

Jacket.....SJT
 Gauge/Wires..... 14/3
 Volts 250V
 Amps 15 Amps
 Color Black
 6 feet..... Product # 4853
 10 feet.... Product # 4854

NEMA 6-15 male Plug Angled Up Hospital Grade



Jacket.....SJT
 Gauge/Wires..... 14/3
 Volts 250V
 Amps 15 Amps
 Color Black
 3 feet..... Product # 4833
 6 feet..... Product # 4834

NEMA 6-20 male Plug to C19 Hospital Grade



Jacket.....SJT Shielded
 Gauge/Wires..... 12/3
 Volts 250V
 Amps 20 Amps
 Color Black
 15 feet.... Product # 9303

Jacket.....SJT
 Gauge/Wires..... 12/3
 Volts 250V
 Amps 20 Amps
 Color Black
 6 feet..... Product # 4857
 10 feet.... Product # 4858

NEMA 6-20 male Plug Angled Up to C19 Hospital Grade



Jacket.....SJT
 Gauge/Wires..... 12/3
 Volts 250V
 Amps 20 Amps
 Color Black
 3 feet..... Product # 4837
 6 feet..... Product # 4851

NEMA Hospital Grade Custom Configurator

Custom Assembly Indoor Cords
Home > Configuration > Custom Assembly Indoor Cords

1000000101: Current lead time is about 2 business days

Step 1. Male Plug

Plug type	No. of wires	Ampereage	Voltage
ALL	ALL	ALL	ALL
NEMA L5-15: 125 Volts, 15 Amps - 2 Pole, 3 Wire NEMA L5-20: 125 Volts, 20 Amps - 2 Pole, 3 Wire NEMA L6-30: 125 Volts, 30 Amps - 2 Pole, 3 Wire NEMA L6-15: 250 Volts, 15 Amps - 2 Pole, 3 Wire NEMA L6-15: 250 Volts, 15 Amps - 2 Pole, 3 Wire			

Step 2. Female Connector

Connector type	No. of wires	Ampereage	Voltage
ALL	ALL	ALL	ALL
NEMA L5-15: 125 Volts, 15 Amps - 2 Pole, 3 Wire NEMA L5-20: 125 Volts, 20 Amps - 2 Pole, 3 Wire NEMA L5-30: 125 Volts, 30 Amps - 2 Pole, 3 Wire NEMA L5-30 Connector (P20) - 125 Volts, 30 Amps - 2 Pole, 3 Wire			

Step 3. Cord Type and Length

*Feet or Meters Cord types show with a valid plug and connector.

3'feet 2'feet 3'feet 4'feet 5'feet	
--	--

Step 4. Cord Options

Please select a cord.

Step 5. Cable Name

Cable name will appear here with valid selections.

110

Please Select A Plug

1100000101

Please Select A Connector

110

Please Select A Cord

Build My Cord

Don't see what you're looking for? Build it with our online custom configuration tool.

5 Page

NEMA Straight Hospital Grade Devices

Hospital Grade (HG) Standards

Plugs, Connectors, Receptacles and Power Cords used in medical applications must have a green dot prominently displayed on the housing surface to indicate conformance with Underwriter Laboratories specifications UL817, UL60601-1 and UL498. Further, UL60601-1 states that all patient care equipment must use power cords with hospital grade attachment plugs.

Hospital Grade wiring devices and cords must meet vigorous material, construction, and testing standards.

1. Prong blades must be of solid brass construction without folding.
2. A retaining strain relief type device must be added to the inside of the plug mold to prevent any potential stress to connections and ensure grounding reliability.
3. Must pass the following stringent UL tests:

NEMA Hospital Grade Plugs

HUBBELL HBL8115V AC Plug NEMA 5-15 Male HG Valise White



Item #: 7198
Manufacturer: Hubbell
Weight: 0.1 lbs

Plug NEMA 5-15 HG
 Housing Style Valise
 Voltage..... 125 Volts
 Amperage..... 15 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range .. .300" - .660" (7.62 - 16.7mm)
 Color White
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.1 lbs

HUBBELL HBL8215C AC Plug NEMA 5-15 Male HG



Item #: 7195
Manufacturer: Hubbell
Weight: 0.2 lbs

Plug NEMA 5-15 HG
 Housing Style Insulgrip
 Voltage..... 125 Volts
 Amperage..... 15 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range230" - .720" (5.8 - 18.3mm)
 Color Black/White
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.2 lbs

HUBBELL HBL8215CAT AC Plug NEMA 5-15 Male Angled HG Clear



Item #: 7197
Manufacturer: Hubbell
Weight: 0.2 lbs

Plug NEMA 5-15 HG
 Plug Angle..... 8-position
 Housing Style Insulgrip
 Voltage..... 125 Volts
 Amperage..... 15 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range250" - .650" (6.4 - 16.6mm)
 Color Transparent
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.2 lbs

HUBBELL HBL8215CT AC Plug NEMA 5-15 Male HG Clear



Item #: 7196
 Manufacturer: Hubbell
 Weight: 0.2 lbs

Plug NEMA 5-15 HG
 Housing Style Insulgrip
 Voltage..... 125 Volts
 Amperage..... 15 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range230" - .720" (5.8 - 18.3mm)
 Color Transparent
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.2 lbs

HUBBELL HBL8315C AC Plug NEMA 5-20 Male HG



Item #: 7206
 Manufacturer: Hubbell
 Weight: 0.2 lbs

Plug NEMA 5-20 HG
 Housing Style Insulgrip
 Voltage..... 125 Volts
 Amperage..... 20 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range230" - .720" (5.8 - 18.3mm)
 Color Black/White
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.2 lbs

HUBBELL HBL8315CAT AC Plug NEMA 5-20 Male Angled HG Clear



Item #: 7210
 Manufacturer: Hubbell
 Weight: 0.2 lbs

Plug NEMA 5-20 HG
 Plug Angle 8-position
 Housing Style Insulgrip
 Voltage..... 125 Volts
 Amperage..... 20 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range250" - .650" (6.4 - 16.6mm)
 Color Transparent
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.2 lbs

HUBBELL HBL8315CT AC Plug NEMA 5-20 Male HG Clear



Item #: 7209
 Manufacturer: Hubbell
 Weight: 0.2 lbs

Plug NEMA 5-20 HG
 Housing Style Insulgrip
 Voltage..... 125 Volts
 Amperage..... 20 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range230" - .720" (5.8 - 18.3mm)
 Color Transparent
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.2 lbs

HUBBELL HBL8364V AC Plug NEMA 5-20 Male HG Valise White



Item #: 7211
 Manufacturer: Hubbell
 Weight: 0.1 lbs

Plug NEMA 5-20 HG
 Housing Style Valise
 Voltage..... 125 Volts
 Amperage..... 20 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range .. .300" - .660" (7.62 - 16.7mm)
 Color White
 Certifications UL, CSA
 Weight 0.1 lbs

HUBBELL HBL8464V AC Plug NEMA 6-20 HG Male Valise White



Item #: 7214
 Manufacturer: Hubbell
 Weight: 0.1 lbs

Plug NEMA 6-20 HG
 Housing Style Valise
 Voltage..... 250 Volts
 Amperage..... 20 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range .. .300" - .660" (7.62 - 16.7mm)
 Color White
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.1 lbs

HUBBELL HBL8666V AC Plug NEMA 6-15 Male Valise White



Item #: 7212
Manufacturer: Hubbell
Weight: 0.1 lbs

Plug NEMA 6-15 HG
 Housing Style Valise
 Voltage..... 250 Volts
 Amperage..... 15 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range... .300" - .660" (7.62 - 16.7mm)
 Color White
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.1 lbs

Plug and Connector Testing

HG Test: Impact Test - A plug or connector wired with the minimum size flexible cord is subjected to an impact from a 10 pound cylindrical weight having a flat face with a 2 inch diameter dropped from a height of 18 inches. After the test, there shall be no breakage or other damage that may affect the function of the device.

HG Test: Mechanical Drop Test - The cord connector is wired to #18 AWG flexible cord and suspended horizontally. It is released so it impacts a hardwood surface 45 inches below the point of suspension. This is repeated for 1,300 cycles. After the test, there shall be no breakage, deformation or other effect that may interfere with the function of the device.

HG Test: 500 Pound Crush Test - A wired plug or connector is placed between two hardwood slabs while subjected to a force which is progressively increased to 500 pounds. After the test, there shall be no breakage, deformation or other effect that may interfere with the function of the device.

HG Test: Strain Relief Test - While assembled to a plug or connector but not wired to the terminals; the cord must remain securely fastened after a straight pull of 30 pounds and a rotary motion within 3 inch circles with a 10 pound force applied for two consecutive hours. Displacement of conductors, insulation and outer jacket of the flexible cord shall not exceed 0.031 inch. There shall be no cuts, rips or tears in the insulation of the cord.

NEMA Straight Blade Hospital Grade Connectors

HUBBELL HBL8119V AC Connector NEMA 5-15 Female Valise White



Item #: 7222
Manufacturer: Hubbell
Weight: 0.1 lbs

Voltage..... 125 Volts AC
 Amperage..... 15 Amps
 Connector..... NEMA 5-15
 Cord Gauge..... 18 - 12 AWG
 Poles / Wires..... 2 Pole, 3 Wire
 Cord Grip Range220 - .660 in.
 Weight 0.1 lbs.
 Color White nylon
 Certifications .. UL/cUL Listed and CSA Certified

HUBBELL HBL8219C AC Connector NEMA 5-15 Female HG



Item #: 7215
Manufacturer: Hubbell
Weight: 0.2 lbs

Cord Connector Material Nylon
 Housing Style Insulgrip
 Voltage..... 125 Volts
 Amperage..... 15 Amps
 Ingress Protection IP20
 Poles / Wires..... 2p / 3w
 Cord Grip Range230" - .720" (5.8 - 18.3mm)
 Color Black/White
 Certifications UL/cUL Listed, CSA Certified
 Weight 0.2 lbs

HUBBELL HBL8219CT AC Connector NEMA 5-15 Female HG Clear



Item #: 7216
Manufacturer: Hubbell
Weight: 0.2 lbs

Voltage..... 125 Volts AC
 Amperage..... 15 Amps
 Connector..... HG NEMA 5-15
 Cord Gauge..... 18 - 10 AWG
 Poles / Wires..... 2 Pole, 3 Wire
 Cord Grip Range230 - .720 in.
 Weight 0.1 lbs.
 Color White nylon
 Certifications .. UL/cUL Listed and CSA Certified

**HUBBELL HBL8319C AC
Connector NEMA 5-20
Female HG**



Item #: 7217
Manufacturer: Hubbell
Weight: 0.2 lbs

Cord Connector Material.....Nylon
Housing StyleInsulgrip
Voltage..... 125 Volts
Amperage..... 20 Amps
Ingress ProtectionIP20
Poles / Wires..... 2p / 3w
Cord Grip Range230" - .720" (5.8 - 18.3mm)
ColorBlack/White
CertificationsUL/cUL Listed, CSA Certified
Weight 0.2 lbs

**HUBBELL HBL8319CT
AC Connector NEMA 5-20
Female HG Clear**



Item #: 7218
Manufacturer: Hubbell
Weight: 0.2 lbs

Voltage..... 125 Volts AC
Amperage..... 20 Amps
Connector..... HG NEMA 5-15/20 T-Slot
Cord Gauge..... 18 - 10 AWG
Poles / Wires.....2 Pole, 3 Wire
Cord Grip Range230 - .720 in.
Weight 0.1 lbs.
ColorWhite and white nylon
Certifications ..UL/cUL Listed and CSA Certified

**HUBBELL HBL8469V AC
Connector NEMA 6-20
Female Valise White**



Item #: 7234
Manufacturer: Hubbell
Weight: 0.1 lbs

Voltage..... 250 Volts AC
Amperage..... 20 Amps
Connector.....NEMA 6-15/20 T-Slot
Cord Gauge..... 18 - 12 AWG
Poles / Wires.....2 Pole, 3 Wire
Cord Grip Range230 - .660 in.
Weight 0.1 lbs.
Color White nylon
Certifications ..UL/cUL Listed and CSA Certified

Stay Online offers quick turns on custom cords using Hubbell Parts. Try our online custom configuration tool today.



Receptacle Testing

HG Test: Abrupt Removal of Plug Test - A steel bodied test plug with blades made of brass is inserted into the receptacle. A 10 pound weight dropped from at least 24 inches, pulls the plug out of the receptacle abruptly. This test is done eight times with the receptacle rotated in different positions to create the greatest stress to the face and contacts. Then, with the receptacle facing down, the grounding contact must retain a 4 ounce grounding pin with a 0.184 inch diameter for one minute. After this test there shall be no breakage of the receptacle that interferes with the receptacle function or to the integrity of the enclosure.

NEMA Hospital Grade Receptacles

HUBBELL HBL8200 AC Receptacle NEMA 5-15 Female Brown Duplex Hospital



Item #: 6538
Manufacturer: Hubbell
Weight: 0.3 lbs

Hospital Grade Receptacle Type Duplex
 Amperage..... 15 Amps
 Voltage..... 125 Volt AC
 ColorBrown
 NEMA designation..... 5-15R
 Horse Power 0.5
 Certification-UL Listed to UL498 File E2186, Guide RTRT Fed Spec WC596G, Meets WD-1 Heavy Duty and WD-6 requirements, Certified to CSA, C22.2, No. 42 file 285.
 Top Material Thermoplastic polyester
 Base Material..... RTP
 Power Contacts04" (1) Brass - Nickel Plated
 Ground Contacts04" (1) Brass - Nickel Plated
 Mounting Strap05" (1.3) Brass - Nickel Plated
 Terminal Screw#10-32 Silicon Bronze (Nickel plate if Neutral)
 Ground Screw #10-32 Silicon Bronze (Green)
 Center Assembly Rivet..... Silicon Bronze
 Auto. Ground Clip..... Stainless Steel
 Mounting Screws Stainless Steel
 Dielectric Voltage ... Withstands 2000V minimum
 Current InterruptingCertified for current interrupting at full rated current
 Temperature RiseMax 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
 Terminal ID ... In accordance with UL498 (brass, White, Green)
 Product ID Ratings permanently molded on device
 FlammabilityUL94 V0 and UL 94-5 VA
 Operating Temp... Maximum continuous 75 deg. C; Minimum -40 deg C (without impact)
 Weight 0.2 lbs.

HUBBELL HBL8200GY AC Receptacle NEMA 5-15 Female Gray Duplex Hospital



Item #: 7187
Manufacturer: Hubbell
Weight: 0.2 lbs

Hospital Grade Receptacle Type Duplex
 Amperage..... 15 Amp
 Voltage..... 125 Volt
 Color Gray
 NEMA designation..... 5-15R
 Horse Power 1.5
 Certification-UL Listed to UL498 File E2186, Guide RTRT Fed Spec WC596G, Meets WD-1 Heavy Duty and WD-6 requirements, Certified to CSA, C22.2, No. 42 file 285.
 Top Material Thermoplastic polyester
 Base Material..... RTP
 Power Contacts04" (1) Brass - Nickel Plated
 Ground Contacts .032" (.8) Brass - Nickel Plated
 Mounting Strap05" (1.3) Brass - Nickel Plated
 Terminal Screw#8-32 Silicon Bronze (Nickel plate if Neutral)
 Ground Screw #8-32 Silicon Bronze (Green)
 Center Assembly Rivet..... Silicon Bronze
 Auto. Ground Clip..... Stainless Steel
 Mounting Screws Stainless Steel
 Dielectric Voltage ... Withstands 2000V minimum
 Current InterruptingCertified for current interrupting at full rated current
 Temperature RiseMax 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
 Terminal ID ... In accordance with UL498 (brass, White, Green)
 Product ID Ratings permanently molded on device
 FlammabilityUL94 V0 and UL 94-5 VA
 Operating Temp... Maximum continuous 75 deg. C; Minimum -40 deg C (without impact)

HUBBELL HBL8200W AC Receptacle NEMA 5-15 Female White Duplex Hospital



Item #: 7188
Manufacturer: Hubbell
Weight: 0.3 lbs

Hospital Grade Receptacle Type Duplex
 Amperage..... 15 Amp
 Voltage..... 125 Volt
 Color White
 NEMA designation..... 5-15R
 Horse Power 1.5
 Certification-UL Listed to UL498 File E2186, Guide RTRT Fed Spec WC596G, Meets WD-1 Heavy Duty and WD-6 requirements, Certified to CSA, C22.2, No. 42 file 285.
 Top Material Thermoplastic polyester
 Base Material..... RTP
 Power Contacts04" (1) Brass - Nickel Plated
 Ground Contacts .032" (.8) Brass - Nickel Plated
 Mounting Strap05" (1.3) Brass - Nickel Plated
 Terminal Screw#8-32 Silicon Bronze (Nickel plate if Neutral)
 Ground Screw #8-32 Silicon Bronze (Green)
 Center Assembly Rivet..... Silicon Bronze
 Auto. Ground Clip..... Stainless Steel
 Mounting Screws Stainless Steel
 Dielectric Voltage ... Withstands 2000V minimum
 Current InterruptingCertified for current interrupting at full rated current
 Temperature RiseMax 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
 Terminal ID ... In accordance with UL498 (brass, White, Green)
 Product ID Ratings permanently molded on device
 FlammabilityUL94 V0 and UL 94-5 VA
 Operating Temp... Maximum continuous 75 deg. C; Minimum -40 deg C (without impact)

**HUBBELL HBL8300 AC
Receptacle NEMA 5-15/20
Female Brown Duplex
Hospital**



**Item #: 3693
Manufacturer: Hubbell
Weight: 0.3 lbs**

Hospital Grade Receptacle Type Duplex
Amperage..... 20 Amps
Voltage..... 125 Volt AC
ColorBrown
NEMA designation.....5-15/20R T-slot
Horse Power 1
Certification-UL Listed to UL498 File E2186,
Guide RTRT Fed Spec WC596G, Meets WD-1
Heavy Duty and WD-6 requirements, Certified to
CSA, C22.2, No. 42 file 285.
Top Material..... Thermoplastic polyester
Base Material..... RTP
Power Contacts04" (1) Brass - Nickel Plated
Ground Contacts04" (1) Brass - Nickel Plated
Mounting Strap05" (1.3) Brass - Nickel Plated
Terminal Screw#10-32 Silicon Bronze (Nickel
plate if Neutral)
Ground Screw #10-32 Silicon Bronze (Green)
Center Assembly Rivet Silicon Bronze
Auto. Ground Clip..... Stainless Steel
Mounting Screws..... Stainless Steel
Dielectric Voltage ... Withstands 2000V minimum
Current InterruptingCertified for current
interrupting at full rated current
Temperature RiseMax 30°C temperature rise
at full rated current after 50 cycles of overload at
150% of rated current at a power factor of 75%.
Terminal ID ... In accordance with UL498 (brass,
White, Green)
Product ID Ratings permanently molded on
device
FlammabilityUL94 V0 and UL 94-5 VA
Operating Temp... Maximum continuous 75 deg.
C; Minimum -40 deg C (without impact)
Weight 0.2 lbs.

**HUBBELL HBL8300GY
AC Receptacle NEMA
5-15/20 Female Gray Duplex
Hospital**



**Item #: 7192
Manufacturer: Hubbell
Weight: 0.2 lbs**

Hospital Grade Receptacle Type Duplex
Amperage..... 20 Amp
Voltage..... 125 Volt
Color Gray
NEMA designation..... 5-15/20R
Horse Power 1.5
Certification-UL Listed to UL498 File E2186,
Guide RTRT Fed Spec WC596G, Meets WD-1
Heavy Duty and WD-6 requirements, Certified to
CSA, C22.2, No. 42 file 285.
Top Material..... Thermoplastic polyester
Base Material..... RTP
Power Contacts04" (1) Brass - Nickel Plated
Ground Contacts .032" (.8) Brass - Nickel Plated
Mounting Strap05" (1.3) Brass - Nickel Plated
Terminal Screw#8-32 Silicon Bronze (Nickel
plate if Neutral)
Ground Screw #8-32 Silicon Bronze (Green)
Center Assembly Rivet Silicon Bronze
Auto. Ground Clip..... Stainless Steel
Mounting Screws..... Stainless Steel
Dielectric Voltage ... Withstands 2000V minimum
Current InterruptingCertified for current
interrupting at full rated current
Temperature RiseMax 30°C temperature rise
at full rated current after 50 cycles of overload at
150% of rated current at a power factor of 75%.
Terminal ID ... In accordance with UL498 (brass,
White, Green)
Product ID Ratings permanently molded on
device
FlammabilityUL94 V0 and UL 94-5 VA
Operating Temp... Maximum continuous 75 deg.
C; Minimum -40 deg C (without impact)

**HUBBELL HBL8300W AC
Receptacle NEMA 5-15/20
Female White Duplex
Hospital**



**Item #: 7194
Manufacturer: Hubbell
Weight: 0.2 lbs**

Hospital Grade Receptacle Type Duplex
Amperage..... 20 Amp
Voltage..... 125 Volt
ColorWhite
NEMA designation..... 5-15/20R
Horse Power 1.5
Certification-UL Listed to UL498 File E2186,
Guide RTRT Fed Spec WC596G, Meets WD-1
Heavy Duty and WD-6 requirements, Certified to
CSA, C22.2, No. 42 file 285.
Top Material..... Thermoplastic polyester
Base Material..... RTP
Power Contacts04" (1) Brass - Nickel Plated
Ground Contacts .032" (.8) Brass - Nickel Plated
Mounting Strap05" (1.3) Brass - Nickel Plated
Terminal Screw#8-32 Silicon Bronze (Nickel
plate if Neutral)
Ground Screw #8-32 Silicon Bronze (Green)
Center Assembly Rivet Silicon Bronze
Auto. Ground Clip..... Stainless Steel
Mounting Screws..... Stainless Steel
Dielectric Voltage ... Withstands 2000V minimum
Current InterruptingCertified for current
interrupting at full rated current
Temperature RiseMax 30°C temperature rise
at full rated current after 50 cycles of overload at
150% of rated current at a power factor of 75%.
Terminal ID ... In accordance with UL498 (brass,
White, Green)
Product ID Ratings permanently molded on
device
FlammabilityUL94 V0 and UL 94-5 VA
Operating Temp... Maximum continuous 75 deg.
C; Minimum -40 deg C (without impact)

**HUBBELL HBL8400 AC
Receptacle NEMA 6-15/20
Female Brown Duplex
Hospital**



Item #: 6046
Manufacturer: Hubbell
Weight: 0.3 lbs

Hospital Grade Receptacle Type Duplex
Amperage..... 20 Amp
Voltage..... 250 Volt
ColorBrown
NEMA designation..... 6-20R
Horse Power2
Certification -UL Listed to UL498 File E2186,
Guide RTRT Fed Spec WC596G, Meets WD-1
Heavy Duty and WD-6 requirements, Certified to
CSA, C22.2, No. 42 file 285.
Top Material Thermoplastic polyester
Base Material..... RTP
Power Contacts04" (1) Brass - Nickel Plated
Ground Contacts ...03" (.8) Brass - Nickel Plated
Mounting Strap05" (1.3) Brass - Nickel Plated
Terminal Screw#8-32 Silicon Bronze (Nickel
plate if Neutral)
Ground Screw #8-32 Silicon Bronze (Green)
Center Assembly Rivet Silicon Bronze
Auto. Ground Clip..... Stainless Steel
Mounting Screws..... Stainless Steel
Dielectric Voltage ... Withstands 2000V minimum
Current Interrupting Certified for current
interrupting at full rated current
Temperature RiseMax 30°C temperature rise
at full rated current after 50 cycles of overload at
150% of rated current at a power factor of 75%.
Terminal ID ... In accordance with UL498 (brass,
White, Green)
Product ID Ratings permanently molded on
device
FlammabilityUL94 V0 and UL 94-5 VA
Operating Temp... Maximum continuous 75 deg.
C; Minimum -40 deg C (without impact)
Weight 0.2 lbs.

**HUBBELL HBL8600 AC
Receptacle NEMA 6-15
Female Brown Duplex
Hospital**



Item #: 6047
Manufacturer: Hubbell
Weight: 0.3 lbs

Hospital Grade Receptacle Type Duplex
Amperage..... 15 Amp
Voltage..... 250 Volt
ColorBrown
NEMA designation..... 6-15R
Horse Power 1.5
Certification -UL Listed to UL498 File E2186,
Guide RTRT Fed Spec WC596G, Meets WD-1
Heavy Duty and WD-6 requirements, Certified to
CSA, C22.2, No. 42 file 285.
Top Material Thermoplastic polyester
Base Material..... RTP
Power Contacts04" (1) Brass - Nickel Plated
Ground Contacts .032" (.8) Brass - Nickel Plated
Mounting Strap05" (1.3) Brass - Nickel Plated
Terminal Screw#8-32 Silicon Bronze (Nickel
plate if Neutral)
Ground Screw #8-32 Silicon Bronze (Green)
Center Assembly Rivet Silicon Bronze
Auto. Ground Clip..... Stainless Steel
Mounting Screws..... Stainless Steel
Dielectric Voltage ... Withstands 2000V minimum
Current Interrupting Certified for current
interrupting at full rated current
Temperature RiseMax 30°C temperature rise
at full rated current after 50 cycles of overload at
150% of rated current at a power factor of 75%.
Terminal ID ... In accordance with UL498 (brass,
White, Green)
Product ID Ratings permanently molded on
device
FlammabilityUL94 V0 and UL 94-5 VA
Operating Temp... Maximum continuous 75 deg.
C; Minimum -40 deg C (without impact)
Weight 0.2 lbs.

HUBBELL CATALOG

SPECIAL ORDERS

Hubbelock® Plugs and Connector Bodies

Description	Plugs	Connector Bodies
Nylon cover, thermoset interior	HBL23014HGB	HBL23001HGB
Armored, epoxy filled, rubber cord grip	HBL23004HG	–

Note: Cord clamp range for plug and connector .300" to .660" (7.6 to 16.8)



HBL23014HGB
Part Number: BP12584

HBL23001HGB
Part Number: BP301254

HBL23004HG
Part Number: BP301903

Explosion Proof Plug

Description	Connector Bodies
Plug, with, epoxy kit, accepts #12 or #14 type SO cable	HBL24312




HBL23004HG
Part Number: BP301254

Wallplates

Description	Catalog Number
Stainless steel 302/304, single-gang	HBL23901HG
Stainless steel 302/304, three-gang for two receptacles	HBL23909HG

Note: Suffix HG or HGB type for hospital use only



HBL23901HG
Part Number: BP301904

HBL23909HG
Part Number: BP301905

Hazardous to Non-hazardous Location Receptacle Conversion Kits

Conversion kits for replacement of explosion proof receptacles listed above, with non-explosion proof receptacles, in the hospital areas formerly classified as hazardous locations and now classified non-hazardous locations due to the change from flammable anesthetizing gases to nonflammable anesthetizing gases.

For Conversion To:

20A, 125V, duplex receptacle (Hubbell HBL830 Series).
Includes adapter ring and stainless steel wall plate for duplex receptacle (receptacle not included).

Catalog Number

HBL24300RKD

20A, 125V, Hospital Hubbellock receptacle (Hubbell HBL23000HG) or 20A, 125V, straight blade single receptacle (Hubbell HBL8310 series).
Includes adapter ring and stainless wall plate for single receptacle (receptacle not included).

HBL24300RKS



HBL24300RKD
Part Number: BP301893



HBL24300RKS
Part Number: BP301907

Receptacles

Description

Black, back wired.

Catalog Number

HBL23000HG



HBL23000HG
Part Number: BP301906

Mobile X-Ray Plugs

Description

Plug, with epoxy kit, less cord clamp

Plug, with cord clamp, less epoxy kit.

*Note: Cord clamp range of plugs with cord clamps .830" to 1.3" (21.1 to 33.0).
50A plugs fit 50A or 60A receptacles.*

Catalog Number

HBL25515 HBL25615

HBL25525 HBL25625



HBL25515
Part Number: BP301908



HBL25525
Part Number: BP301731



HBL25615
Part Number: BP301255



HBL25625
Part Number: BP301257

Accessory

Description

Box stamped steel 8" x 8" x 4" (203.2 x 203.2 x 101.6), accommodates 50A and 60A mobile X-ray receptacles.
Knockout sizes 1¼", 1½" and 2".

Catalog Number

HBL25509



HBL25509
Part Number: BP301909

Mobile X-Ray Receptacles

Description

Receptacle with stainless steel plate assembly

Receptacle with cast aluminum plate assembly.

Catalog Number

HBL25505

HBL25503

HBL25605

HBL25603



HBL25505
Part Number: BP301912



HBL25605
Part Number: BP301910



HBL25503
Part Number: BP301911



HBL25603
Part Number: BP301730

WHEN HAVING THE WRONG POWER CORD ISN'T AN OPTION.

Quality first with our **world-class** QMS.

stayonline.com



 **StayOnline**[®]
The Power Cord Manufacturer

888 346-4688



Medical Grade Product Catalog
Medical_Catalog_revision_A
28 October 2016

Copyright © 2016 Stay Online Corp.